



*J D Jones & Co (P) Ltd*



## Pacmaan<sup>®</sup> NA 755

A high grade graphite fibre yarn packing reinforced with Inconel wire impregnated with a special graphite mix in interlock braid

- A universal plant wide multi-service packing
- Very low co-efficient of friction, high thermal conductivity and sliding velocity, runs almost frictionless without any shaft wear
- Excellent resistance to chemicals and hardening thereof
- Structural strength and cross-sectional density of the packing helps reduce maintenance work
- Can be used as an anti-extrusion rings or bull ring in combination with softer packings, even in abrasive media

*Available in rope and ring form*

|                                     |   |
|-------------------------------------|---|
| <b>Service Media and Conditions</b> | Superheated steam, strong chemicals, thermic fluid, acids and alkali, oils and solvents, boiler feed water and condensate, hot tar, SO <sub>2</sub> and SO <sub>3</sub> , fuel oil/lube oil, hydrocarbons etc |
| <b>Temperature</b>                  | -240°C to 650°C   |
| <b>Pressure</b>                     | 300 bar (static), 30 bar (rotary)   |
| <b>Shaft Speed</b>                  | 25 m/sec (rotary)   |
| <b>pH</b>                           | 0 to 14   |
| <b>Applications</b>                 | Pump, valves, agitators, mixers   |