



J D Jones & Co (P) Ltd



Pacmaan[®] NA 781FG

A pure PTFE filament packing impregnated with PTFE

- Manufactured from the purest PTFE yarns to give a soft resilient packing with high dimensional strength, low coefficient of friction, good chemical resistance and inertness to most media
- Special PTFE impregnation, the packing contains no oil
- Ideal for valves and slow shaft speed applications
- Food Grade certified as per Commission Regulation (EU) No 10/2011 of 14 January 2011 and Article 3 of European Regulation No. 1935/2004 and Regulation (EC) No 1935 / 2004

Available in rope and ring form

| | |
|-------------------------------------|---|
| Service Media and Conditions | Highly corrosive chemicals, ammonia charge pumps and carbonate recycle pumps, strong as well as weak acid and alkali, chemicals, foodstuffs, pharmaceutical industry applications, drinking water, hydrogen etc |
| Temperature | -200°C to 280°C |
| Pressure | 200 bar (static), 20 bar (rotary), 175 bar (reciprocating) |
| Shaft Speed | 5 m/sec (rotary), 2 m/sec (reciprocating) |
| pH | 0 to 14 |
| Applications | Valves, plunger pumps, slow rotary/reciprocating pumps, agitators, mixers, filters, blenders, cookers, vacuum dryers etc |